



EASTMAN WORLD

Welcome to Eastman World - Your Global Partner in Energy Solutions!





LITHIUM BATTERIES

WALL MOUNTED | FLOOR MOUNT
RACK TYPE LITHIUM ENERGY STORAGE SYSTEM

MADE IN INDIA

Eastman Introduction

Founded in 2006

Established in 2006, Eastman Auto & Power Limited is a well-known name in the field of solar energy, energy storage, and power electronics, boasting a USD 420 million revenue and a dedicated workforce of over 3,000 professionals. Building on the group's decades-long success and maintaining the trust of our partners, Mr. Jagdish Rai Singal ventured into the future of energy with Eastman Auto & Power Limited.

Today, the business spans over 50 countries across Asia, the Middle East, Europe, Africa, the Caribbean, Central America, North America, and South America, providing the world with cutting-edge products that have set new benchmarks in their respective segments. With products reaching more than 100 countries, we are driven by innovation to continually set industry standards, ensuring uninterrupted power supply for residential, commercial, and industrial applications.










MADE IN INDIA

Connection Diagram



RESIDENTIAL ES25.6V LiFePO4 (Lithium **Phosphate**) **ENERGY STORAGE BATTERY**

Introduction

Upgrade your Energy Storage with our Lithium Phosphate Battery. Stay informed with real-time operation status via the LCD Screen, ensuring total control and efficiency for your power requirements.

Product Features

- · Real-time monitoring of operation status by LCD
- Intelligent Air Cooling & Heat dissipation.
- RS485/CAN Communication for connecting more batteries in parallel.
- Installation option: Wall mount.

Certifications











Product Specifications

| Model | ES25.6-100LP | ES25.6-230LP | | |
|---|---|--------------|--|--|
| Array Mode | | 8S | | |
| Nominal Energy (kWh) | 2.5 | 5.8 | | |
| Nominal Voltage (V) | | 25.6 | | |
| Charge Voltage (V) | 29.2 | | | |
| Discharge Cut-off Voltage (V) | 21 | | | |
| Standard Charging Current(A) | 20 | 46 | | |
| Max. Continuous Charging Current (A) | | 100 | | |
| Max. Continuous Discharging Current (A) | | 100 | | |
| Cycle Life | 6000 Cycles @80% DOD @25°C @0.2C/0.2C | | | |
| Communication Mode | RS485/CAN, RS232, RS485/RS485 | | | |
| Parallel Connection | Yes, upto 15 units | | | |
| Operating Temp | Charging: 0~60°C; Discharging: -10°C~65°C | | | |
| Size(LxWxH) mm | 440x170x350 | 560x470x170 | | |
| Net Weight (kg) | ~23 | ~45 | | |
| Gross Weight (kg) | ~25 | ~47 | | |
| Warranty | 5 Years | | | |
| Altitude | ≤4000m | | | |
| Humidity | <90%RH | | | |
| Shelf Temperature | 10°C~60°C | | | |
| Design Life | 10+ Years at 25°C/77°F | | | |






RESIDENTIAL ES51.2V LiFePO4 (Lithium **Phosphate**) **ENERGY STORAGE BATTERY**



MADE IN INDIA

Connection Diagram



Introduction

Upgrade your Energy Storage with our Lithium Phosphate Battery. Stay informed with real-time operation status via the LCD Screen, ensuring total control and efficiency for your power requirements.

Product Features

- Real-time monitoring of operation status by LCD
- Intelligent Air Cooling & Heat dissipation.
- RS485/CAN Communication for connecting more batteries in parallel.
- Installation option: Wall mount.

Certifications









UN38.3 UN 3480

Product Specifications

| Model | ES51.2-100LP | ES51.2-230LP | |
|---|---|--------------|--|
| Array Mode | 16 | S | |
| Nominal Energy (kWh) | 5.1 | 11.7 | |
| Nominal Voltage (V) | 51.2 | | |
| Charge Voltage (V) | 58.4 | | |
| Discharge Cut-off Voltage (V) | 42 | | |
| Standard Charging Current(A) | 20 | 46 | |
| Max. Continuous Charging Current (A) | 100 | 200 | |
| Max. Continuous Discharging Current (A) | 100 | 200 | |
| Cycle Life | 6000 Cycles @80% DOD @25°C @0.2C/0.2C | | |
| Communication Mode | RS485/CAN, RS232, RS485/RS485 | | |
| Parallel Connection | Yes, upto 15 units | | |
| Operating Temp | Charging: 0~60°C; Discharging: -10°C~65°C | | |
| Size(LxWxH) mm | 560x470x170 | 670x485x244 | |
| Net Weight (kg) | ~41 | ~93 | |
| Gross Weiġht (kg) | ~43 | ~106 | |
| Warranty | 5 Years | | |
| Altitude | ≤4000m | | |
| Humidity | <90%RH | | |
| Shelf Temperature | 10°C~60°C | | |
| Design Life | 10+ Years at 25°C/77°F | | |
| | | | |



RESIDENTIAL ES51.2V LiFePO4 (Lithium Phosphate) ENERGY STORAGE BATTERY



MADE IN INDIA

Certifications












Structural Part Description







Product Specifications

Introduction

Upgrade your Energy Storage with our Lithium Phosphate
Battery. Stay informed with real-time operation status via the
LCD Screen, ensuring total control and efficiency for your power
requirements.

Product Features

- LCD Display for monitoring energy storage, power data and operating status.
- High-Quality LiFePo4 Battery for Deep Cycle and Long Lifespan.
- Metal Casing that ensures waterproof and explosion-proof safety.
- External Main Switch to reduce product power consumption and improve safety.
- Mobile bottom wheels designed for easy installation across various locations with ease.
- In-built BMS for Over-Voltage, Over-Load and Over-Temperature protection.
- Compatible-It can be connected to different types of loads within the voltage range.
- Installation option: Floor mount.

| Model | ES51.2-280LP | | |
|---|---|--|--|
| Array Mode | 165 | | |
| Nominal Energy (kWh) | 14.3 | | |
| Nominal Voltage (V) | 51.2 | | |
| Charge Voltage (V) | 58.4 | | |
| Discharge Cut-off Voltage (V) | 42 | | |
| Standard Charging Current(A) | 56 | | |
| Max. Continuous Charging Current (A) | 200 | | |
| Max. Continuous Discharging Current (A) | 200 | | |
| Cycle Life | 6000 Cycles @80% DOD @25°C @0.5C/0.5C | | |
| Communication Mode | RS485/CAN, RS232, RS485/RS485 | | |
| Parallel Connection | Yes, upto 15 units | | |
| Operating Temp | Charging: 0~60°C; Discharging: -10°C~65°C | | |
| Size(LxWxH) mm | 750x580x279 | | |
| Net Weight (kg) | ~113 | | |
| Gross Weight (kg) | ~128 | | |
| Warranty | 5 Years | | |
| Altitude | ≤4000m | | |
| Humidity | <90%RH | | |
| Shelf Temperature | 10°C~60°C | | |
| Design Life | 10+ Years at 25°C/77°F | | |



RACK TYPE LITHIUM

ENERGY STORAGE BATTERY

MADE IN INDIA

Connection Diagram



Certifications



Applications

- Telecom
- UPS
- Emergency Light
- Solar System
- Wind Power

Introduction

Optimize your Energy Solution with our Rack-Type Energy Storage. Featuring advanced warning functions for secure and dependable operation in all conditions.

Product Features

- Standardized Design: Our 3U and 4U Standardized case ensures broad applicability.
- Enhanced Energy Capacity: Support multiple parallel battery usage to meet high energy demands.
- Intelligent Lithium Battery Management System: Equipped with RS485 communication, offers real-time battery monitoring and customizable protection parameters such as charge & discharge.
- Balancing: Automatic collection of battery single series voltage, pressure difference up to 30 Mega Volt (can be set) with an automatic start equalization function.
- Warning Function: Advanced warning functions, including Overcharge, Over-Discharge, Over-Current, High-Temperature and Low-Temperature alerts reducing potential safety risks.

Product Specifications

| Model | ES51.2-100BS | ES51.2-400BS | |
|---|---|-----------------------------|--|
| Array Mode | 16S | 16S x4 (Modu l e) | |
| Nominal Energy (kWh) | 5.1 | 20.0 | |
| Nominal Voltage (V) | 51.2 | | |
| Charge Voltage (V) | 58.4 | | |
| Discharge Cut-off Voltage (V) | 42 | | |
| Standard Charging Current(A) | 20 | 20x4 | |
| Max. Continuous Charging Current (A) | 100 | 100x4 | |
| Max. Continuous Discharging Current (A) | 100 | 100x4 | |
| Cycle Life | 6000 Cycle @80% DOD @25°C @0.2C/0.2C | | |
| Communication Mode | RS485/CAN | | |
| Operating Temp | Charging: 0~60°C; Discharging: -10°C~65°C | | |
| Size(LxWxH) mm | 520x495x175 | 600x600x1000 (with cabinet) | |
| Net Weight (kg) | ~44 | ~200 | |
| Gross Weiġht (kg) | ~46 | ~210 | |
| Warranty | 5 Years | | |
| Altitude | ≤4000m | | |
| Humidity | <90%RH | | |
| Shelf Temperature | 10°C~60°C | | |
| Design Life | 10+ Years at 25°C/77°F | | |



RACK TYPE LITHIUM ENERGY STORAGE SYSTEM

| Sr. No. | Item Description | Referenace Image | QTY. | UOM |
|---------|--|------------------|------|------|
| 1 | Rack 4P with Four Wheels and one AC Extension Board | | 1 | Nos. |
| 2 | Battery Pack | Colman | 4 | Nos. |
| 3 | Connection Cable Negative Terminal | | 3 | Nos. |
| 4 | Connection Cable Positive Terminal | | 3 | Nos. |
| 5 | Rack To Inverter Connection Cable Negative Terminal | | 1 | Nos. |
| 6 | Rack To Inverter Connection Cable Positive Terminal | 0 | 1 | Nos. |
| 7 | Ph Head M6*12 | Q T | 16 | Nos. |



EASTMAN AUTO & POWER LTD.

572, Udyog Vihar, Phase - V, Gurugram, Haryana - 122016, India, Tel. : +91-124-4682650

AMPS MIDDLE EAST FZ LLC

#703, 7th Floor, De ra Twin Tower, Baniyas Square, De ra, Dubai (UAE)

EASTMAN NEW ENERGY PRIVATE LIMITED

Plot No 264, Sector-7, IMT Manesar, District - Gurugram Haryana-122050, India