











**Max PRO**  
3.6  
SOLAR  
INVERTER


**EM-3624 MP**  
4000W



 Power Factor 1	 Max PV Array 5000 W	 MPPT Range 120~450 VDC	 Solar Charge Current 120 A				
 Lithium Compatible	Yes	 Wifi	Built-in	 Detachable Screen	Yes	 Parallel Function	No

### Special Features :

- Detachable LCD control module with various communications
- Built-in Wifi for mobile monitoring (Android & IOS App is available)
- Supports USB On-the-Go function
- Reserved communication port for BMS
- Battery independent design
- Battery equalization extends lifecycle
- User-friendly LCD operation
- Replaceable fan design for ease of maintenance





# SOLAR INVERTER

MODEL	EM-3624 MP
Rated Power	4000VA / 4000W
<b>INPUT</b>	
Voltage	230 VAC
Selectable Voltage Range	170-280 VAC (For Personal Computers) ; 90-280 VAC (For Home Appliances)
Frequency Range	50 Hz/60 Hz (Auto sensing)
<b>OUTPUT</b>	
AC Voltage Regulation (Batt. Mode)	230 VAC $\pm$ 5%
Surge Power	8000VA
Efficiency (Peak)	90% ~ 93%
Transfer Time	10 ms (For Personal Computers) ; 20 ms (For Home Appliances)
Waveform	Pure sine wave
<b>BATTERY</b>	
Battery Voltage	24 VDC
Floating Charge Voltage	27 VDC
Overcharge Protection	33 VDC
<b>SOLAR CHARGER &amp; AC CHARGER</b>	
Solar Charger Type	MPPT
Maximum PV Array Power	5000W
MPPT Range @ Operating Voltage	120 ~ 450 VDC
Maximum PV Array Open Circuit Voltage	500 VDC
Maximum Solar Charge Current	120 A
Maximum AC Charge Current	100 A
Maximum Charge Current	120 A
<b>PHYSICAL</b>	
Dimension D x W x H (mm)	115 x 300 x 400
Net Weight (kgs)	9
Communication Interface	USB/RS232/RS485/Wifi/Dry-contact
<b>OPERATING ENVIRONMENT</b>	
Humidity	5% to 95% Relative Humidity (Non-condensing)
Operating Temperature	-10°C to 50°C
Storage Temperature	-15°C to 60°C

\*Product specification are subject to change without prior notice.